

TECHNICAL INFORMATION BULLETIN

EYE Cera Arc Natural Red TP

LAMP TYPE : Ceramic Metal Halide Lamp
CMT70F/NR

PERFORMANCE DATA

Initial luminous flux at rated wattage after 100hrs. Burning	(lm)	:	4,900
Lamp Lumen Efficacy	(lm/W)	:	70
Rated average life	(hrs)	:	9,000
Warm up time	(min)	:	4
Restarting time	(min)	:	15 max.
Correlated colour temperature	(K)	:	3,600
CIE chromaticity	x =	:	0.380
	y =	:	0.360
Colour rendering index	(Ra)	:	92
Burning Position		:	Any

ELECTRICAL CHARACTERISTICS

Nom. Lamp wattage EM	(W)	:	70
Nom. Lamp voltage EM	(V)	:	90
Nom. Lamp current EM	(A)	:	0.95
Current crest factor		:	1.8 max.
Max. starting current	(A)	:	1.50
Compatible Ballast		:	W Metal halide ballast with ignit
Min. starting voltage (RMS)	(V)	:	198
Max. open circuit voltage	(V)	:	280

PHYSICAL DESCRIPTION

Base designation		:	E27
Bulb designation		:	T30 (30mm dia.)
Bulb material		:	Hard glass
Bulb finish		:	Frosted (UV-cut coating)
Arc tube material		:	Alumina
Mercury(Hg)Content	(mg)	:	9.2
Overall Length	(mm)	:	130 max.
Light Centre Length	(mm)	:	-
Effective Arc Length	(mm)	:	-
Bulb Temp. limit	(°C)	:	430
Base Temp. limit	(°C)	:	280
Eccentricity Base to bulb axis	(°)	:	2° max.
Fixture requirement		:	Open fixture permissible
Life to 5% failures	(hr)	:	3100
Life to 10% failures (hr)	(hr)	:	4600
Life to 20% failures (hr)	(hr)	:	6500
Life to 50% failures (hr)	(hr)	:	9000
Lumen Maintenance 5000h	(%)	:	78

