

TECHNICAL INFORMATION BULLETIN

EYE Cera Arc 2800 T

LAMP TYPE : Ceramic Metal Halide Lamp
CMT70/LW928/G12

PERFORMANCE DATA

Initial luminous flux at rated wattage after 100hrs. Burning	(lm)	:	6,300
Lamp Lumen Efficacy	(lm/W)	:	86
Rated average life	(hrs)	:	12,000
Warm up time	(min)	:	4
Restarting time	(min)	:	15 max.
Correlated colour temperature	(K)	:	2,800
CIE chromaticity	x =	:	0.450
	y =	:	0.400
Colour rendering index	(Ra)	:	93
	(R9)	:	40
Burning Position		:	Any

ELECTRICAL CHARACTERISTICS

Nom. Lamp wattage	(W)	:	73
Nom. Lamp voltage	(V)	:	85
Nom. Lamp current	(A)	:	0.86
Current crest factor		:	1.4 max.
Max. starting current	(A)	:	1.89
Compatible Ballast		:	EYE Electronic Ballast
Min. starting voltage (RMS)	(V)	:	280
Max. open circuit voltage	(V)	:	-

PHYSICAL DESCRIPTION

Base designation		:	G12
Bulb designation		:	T19 (19mm dia.)
Bulb material		:	Quartz glass
Bulb finish		:	Clear (UV-cut coating)
Arc tube material		:	Alumina
Mercury(Hg)Content	(mg)	:	6.4
Overall Length	(mm)	:	103 max.
Light Centre Length	(mm)	:	56
Effective Arc Length	(mm)	:	6
Bulb Temp. limit	(°C)	:	650
Base Temp. limit	(°C)	:	280
Eccentricity Base to bulb axis	(°)	:	2° max.
Fixture requirement		:	Enclosed fixture required
Life to 5% failures	(hr)	:	4100
Life to 10% failures (hr)	(hr)	:	6100
Life to 20% failures (hr)	(hr)	:	8600
Life to 50% failures (hr)	(hr)	:	12000
Lumen Maintenance 5000h	(%)	:	82

