

TECHNICAL INFORMATION BULLETIN

EYE Cera Arc PAR20

LAMP TYPE : Ceramic Metal Halide Lamp
CM35P20F/LW

PERFORMANCE DATA

Initial luminous flux at rated wattage after 100hrs. Burning	(lm)	:	1,950
Lamp Lumen Efficacy	(lm/W)	:	50
Beam angle		:	23
Peak intensity		:	7,500
Rated average life	(hrs)	:	9,000
Warm up time	(min)	:	3
Restarting time	(min)	:	15 max.
Correlated colour temperature	(K)	:	3,000
CIE chromaticity	x =	:	0.432
	y =	:	0.392
Colour rendering index	(Ra)	:	90
Burning Position		:	Any

ELECTRICAL CHARACTERISTICS

Nom. Lamp wattage	(W)	:	39
Nom. Lamp voltage	(V)	:	85
Nom. Lamp current	(A)	:	0.46
Current crest factor		:	1.4 max.
Max. starting current	(A)	:	1.06
Compatible Ballast		:	EYE Electronic Ballast
Min. open circuit voltage	(V)	:	280
Max. open circuit voltage	(V)	:	—

PHYSICAL DESCRIPTION

Base designation		:	E27/27
Bulb designation		:	PAR20
Bulb material		:	Hard glass
Bulb finish		:	Aluminium coating
Bulb finish (Front glass)		:	UV-cut coating
Arc tube material		:	Alumina
Mercury(Hg)Content	(mg)	:	3.4
Overall Length	(mm)	:	90 max.
Light Centre Length	(mm)	:	—
Effective Arc Length	(mm)	:	5
Bulb Temp. limit	(°C)	:	300
Base Temp. limit	(°C)	:	200
Eccentricity Base to bulb axis	(°)	:	2° max.
Fixture requirement		:	Open fixture permissible
Life to 5% failures	(hr)	:	3100
Life to 10% failures (hr)	(hr)	:	4600
Life to 20% failures (hr)	(hr)	:	6500
Life to 50% failures (hr)	(hr)	:	9000

