

TECHNICAL INFORMATION BULLETIN

EYE Multi-Hi-Ace

LAMP TYPE : Metal Halide Lamp

MF125LE/BUH

PERFORMANCE DATA

Initial luminous flux at rated wattage after 100hrs. Burning	(lm)	:	8,500
Lamp Lumen Efficacy	(lm/W)	:	68
Mean lumens at 10 hrs/start	(lm)	:	6,800
Rated average life	(hrs)	:	9,000
Warm up time	(min)	:	4
Restarting time	(min)	:	15
Correlated colour temperature	(K)	:	4,200
CIE chromaticity	x =	:	0.390
	y =	:	0.380
Burning Position		:	BUH \pm 105°

ELECTRICAL CHARACTERISTICS

Nom. Lamp wattage EM	(W)	:	125
Nom. Lamp voltage EM	(V)	:	125
Nom. Lamp current EM	(A)	:	1.15
Current crest factor		:	1.8 max.
Min. starting voltage (RMS)	(V)	:	198
Min. starting voltage (PEAK)	(V)	:	280

PHYSICAL DESCRIPTION

Base designation		:	E27
Bulb designation		:	BT70 (70mm Dia.)
Bulb material		:	Hard glass
Bulb finish		:	Phosphor coated
Arc tube material		:	Quartz
Mercury(Hg)Content	(mg)	:	14.5
Overall Length	(mm)	:	178 max.
Light Centre Length	(mm)	:	--
Effective Arc Length	(mm)	:	--
Bulb Temp. limit	(°C)	:	400
Base Temp. limit	(°C)	:	210
Eccentricity Base to bulb axis	(°)	:	3° max.
Life to 5% failures	(hr)	:	3100
Life to 10% failures (hr)	(hr)	:	4600
Life to 20% failures (hr)	(hr)	:	6500
Life to 50% failures (hr)	(hr)	:	9000
Lumen Maintenance 5000h	(%)	:	70

