

TECHNICAL INFORMATION BULLETIN

EYE Multi White Ace

LAMP TYPE : Metal Halide Lamp
MT250SX/BH/LU

PERFORMANCE DATA

Initial luminous flux at rated wattage after 100hrs. Burning	(lm)	:	20,000
Lamp Lumen Efficacy	(lm/W)	:	74
Mean lumens at 10 hrs/start	(lm)	:	16,000
Rated average life	(hrs)	:	10,000
Warm up time	(min)	:	4
Restarting time	(min)	:	15
Correlated colour temperature	(K)	:	4,200
CIE chromaticity	x =	:	0.376
	y =	:	0.396
Colour rendering index	(Ra)	:	65
Burning Position		:	BH $\pm 15^\circ$

ELECTRICAL CHARACTERISTICS

Nom. Lamp wattage EM	(W)	:	270
Nom. Lamp voltage EM	(V)	:	100
Nom. Lamp current EM	(A)	:	3.00
Current crest factor		:	1.8 max.
Max. starting current	(A)	:	5.20
Compatible Ballast		:	250W HPSL ballast with igniter
Min. starting voltage (RMS)	(V)	:	198
Min. starting voltage (PEAK)	(V)	:	280

PHYSICAL DESCRIPTION

Base designation		:	E40
Bulb designation		:	TT55(55mm Dia.)
Bulb material		:	Hard glass
Bulb finish		:	Clear
Arc tube material		:	Quartz
Mercury(Hg)Content	(mg)	:	35
Overall Length	(mm)	:	257 max.
Light Centre Length	(mm)	:	150
Effective Arc Length	(mm)	:	33
Bulb Temp. limit	($^\circ\text{C}$)	:	400
Base Temp. limit	($^\circ\text{C}$)	:	210
Eccentricity Base to bulb axis	($^\circ$)	:	3° max.
Life to 5% failures	(hr)	:	3400
Life to 10% failures (hr)	(hr)	:	5100
Life to 20% failures (hr)	(hr)	:	7200
Life to 50% failures (hr)	(hr)	:	10000
Lumen Maintenance 5000h	(%)	:	70

