

TECHNICAL INFORMATION BULLETIN

EYE Multi-Metal

LAMP TYPE : Metal Halide Lamp
MF400X/BUP/LU

PERFORMANCE DATA

Initial luminous flux at rated wattage after 100hrs. Burning	(lm)	:	38,000
Lamp Lumen Efficacy	(lm/W)	:	95
Mean lumens at 10 hrs/start	(lm)	:	28,500
Rated average life	(hrs)	:	10,000
Warm up time	(min)	:	4
Restarting time	(min)	:	15
Correlated colour temperature	(K)	:	3,800
CIE chromaticity	x =	:	0.394
	y =	:	0.398
Colour rendering index	(Ra)	:	70
Burning Position		:	BU $\pm 15^\circ$

ELECTRICAL CHARACTERISTICS

Nom. Lamp wattage EM	(W)	:	400
Nom. Lamp voltage EM	(V)	:	100
Nom. Lamp current EM	(A)	:	4.60
Current crest factor		:	1.8 max.
Max. starting current	(A)	:	7.50
Compatible Ballast		:	400W HPSL ballast with igniter
Min. starting voltage (RMS)	(V)	:	198
Min. starting voltage (PEAK)	(V)	:	280

PHYSICAL DESCRIPTION

Base designation		:	E40
Bulb designation		:	BT116 (116mm Dia.)
Bulb material		:	Hard glass
Bulb finish		:	Phosphor coated
Arc tube material		:	Quartz
Mercury(Hg)Content	(mg)	:	44
Overall Length	(mm)	:	292 max.
Light Centre Length	(mm)	:	--
Effective Arc Length	(mm)	:	--
Bulb Temp. limit	($^\circ\text{C}$)	:	400
Base Temp. limit	($^\circ\text{C}$)	:	210
Eccentricity Base to bulb axis	($^\circ$)	:	3° max.
Life to 5% failures	(hr)	:	3400
Life to 10% failures (hr)	(hr)	:	5100
Life to 20% failures (hr)	(hr)	:	7200
Life to 50% failures (hr)	(hr)	:	10000
Lumen Maintenance 5000h	(%)	:	70

