

TECHNICAL INFORMATION BULLETIN

EYE Multi-Metal

LAMP TYPE : Metal Halide Lamp
MT2000B-BH-L

PERFORMANCE DATA

Initial luminous flux at rated wattage after 100hrs. Burning	(lm)	:	200,000
Lamp Lumen Efficacy	(lm/W)	:	100
Mean lumens at 10 hrs/start	(lm)	:	160,000
Rated average life	(hrs)	:	9,000
Warm up time	(min)	:	4
Restarting time	(min)	:	15
Correlated colour temperature	(K)	:	4,200
CIE chromaticity	x =	:	0.376
	y =	:	0.396
Colour rendering index	(Ra)	:	65
Burning Position		:	BH ± 60°

ELECTRICAL CHARACTERISTICS

Nom. Lamp wattage EM	(W)	:	2,000
Nom. Lamp voltage EM	(V)	:	230
Nom. Lamp current EM	(A)	:	9.20
Current crest factor		:	1.8 max.

PHYSICAL DESCRIPTION

Base designation		:	E40
Bulb designation		:	TT100 (100mm Dia.)
Bulb material		:	Hard glass
Bulb finish		:	Clear
Arc tube material		:	Quartz
Mercury(Hg)Content	(mg)	:	205
Overall Length	(mm)	:	435 max.
Light Centre Length	(mm)	:	255
Effective Arc Length	(mm)	:	135
Bulb Temp. limit	(°C)	:	500
Base Temp. limit	(°C)	:	210
Eccentricity Base to bulb axis	(°)	:	3° max.
Life to 5% failures	(hr)	:	3100
Life to 10% failures (hr)	(hr)	:	4600
Life to 20% failures (hr)	(hr)	:	6500
Life to 50% failures (hr)	(hr)	:	9000
Lumen Maintenance 5000h	(%)	:	70

