

EYE CERA ARC 5500K




Fig.1

PHYSICAL DATA AND CHARACTERISTICS

| Type | Watts (W) | Bulb | Base | Bulb Finish | Std. Pkg. Qty. | Colour Temp. (K) | Lamp | | Initial Lumens (lm) | Ra | Rated Av. Life (hrs) | Burning Position | Fig. No. | Ref.* |
|-----------------------------------------------------------------|-----------|------|------|-------------|----------------|------------------|-------------|-------------|---------------------|----|----------------------|------------------|----------|-------|
| | | | | | | | Voltage (V) | Current (A) | | | | | | |
| EYE CERA ARC 5500K TP - Tubular Protected E27 screw base | | | | | | | | | | | | | | |
| CMT150/N | 150 | T30 | E27 | Clear | 12 | 5500 | 90 | 1.67 | 12500 | 95 | 9000 | Any | 1 | ECG |
| CMT150F/N | 150 | T30 | E27 | Diffused | 12 | 5500 | 90 | 1.67 | 12000 | 95 | 9000 | Any | 1 | ECG |

* Lamps marked ECG in the Ref. column must be used with electronic ballasts manufactured by or approved by Iwasaki Electric to ensure correct operation.

FEATURES

- Ra: 95, high colour rendering.
- Provides approx. 13% higher lumens than other high colour temperature CRI metal halide lamps.
- R9: ≥ 70 , high red colour rendering.
- UV reduction coating on outer bulb prevents lit objects from fading and maintains high output with polycarbonate lenses.

