

TECHNICAL INFORMATION BULLETIN

EYE Cera Arc 2800K TP

LAMP TYPE : Ceramic Metal Halide Lamp
CMT150/LW928

PERFORMANCE DATA

Initial luminous flux at rated			
wattage after 100h burning	(lm)	:	13,500
Lamp lumen efficacy	(lm/W)	:	90
Rated average life	(h)	:	12,000
Warm up time	(min)	:	4
Restarting time	(min)	:	15 max.
Correlated colour temperature	(K)	:	2,800
CIE chromaticity	x	:	0.45
	y	:	0.40
Colour rendering index	(Ra)	:	95
Burning position		:	Any
Survival factor at 2,000h	(%)	:	98
4,000h	(%)	:	94
6,000h	(%)	:	87
8,000h	(%)	:	78
12,000h	(%)	:	50
Lumen Maintenance factor at 2,000h	(%)	:	81
4,000h	(%)	:	76
6,000h	(%)	:	74
8,000h	(%)	:	72
12,000h	(%)	:	70
Energy Efficiency Label		:	A+
Weighted Energy consumption (kWh/1000h)		:	165

Lamp wattage (Nominal)


Lamp wattage (Nominal)	(W)	:	150
Lamp wattage (Rated)	(W)	:	150
Lamp voltage	(V)	:	90
Lamp current	(A)	:	1.67

BALLAST AND IGNITOR INFORMATION

Compatible ballast	:	IWASAKI Specified
--------------------	---	-------------------

PHYSICAL DESCRIPTION

Base designation	:	E27
Bulb designation	:	T30 (30mm dia.)
Bulb material	:	Hard glass
Bulb finish	:	Clear (UV-cut coating)
Arc tube material	:	Alumina
Mercury(Hg) content	(mg)	13.5
Overall length	(mm)	145 max.
Light centre length (Nominal)	(mm)	97
Effective arc length (Nominal)	(mm)	10



LUMINAIRE DESIGN REQUIREMENTS

Bulb Temp. limit	(°C)	:	400
Base Temp. limit	(°C)	:	190
open / enclosed		:	Open fixture permissible

