

TECHNICAL INFORMATION BULLETIN

EYE Cera Arc 2500K TP

LAMP TYPE : Ceramic Metal Halide Lamp
CMT70F/LW925

PERFORMANCE DATA

Initial luminous flux at rated wattage after 100h burning	(lm)	:	5,400
Lamp lumen efficacy	(lm/W)	:	74
Rated average life	(h)	:	20,000
Warm up time	(min)	:	4
Restarting time	(min)	:	15 max.
Correlated colour temperature	(K)	:	2,500
CIE chromaticity	x	:	0.47
	y	:	0.41
Colour rendering index	(Ra)	:	93
Burning position		:	Any
Survival factor at 2,000h	(%)	:	99
4,000h	(%)	:	97
6,000h	(%)	:	95
8,000h	(%)	:	91
12,000h	(%)	:	82
16,000h	(%)	:	68
20,000h	(%)	:	50
Lumen Maintenance factor at 2,000h	(%)	:	86
4,000h	(%)	:	80
6,000h	(%)	:	78
8,000h	(%)	:	75
12,000h	(%)	:	73
16,000h	(%)	:	71
20,000h	(%)	:	70
Energy Efficiency Label		:	A
Weighted Energy consumption (kWh/1000h)		:	80

Lamp wattage (Nominal)


Lamp wattage (Nominal)	(W)	:	70
Lamp wattage (Rated)	(W)	:	73
Lamp voltage	(V)	:	85
Lamp current	(A)	:	0.86

BALLAST AND IGNITOR INFORMATION

Compatible ballast : IWASAKI Specified


PHYSICAL DESCRIPTION


Base designation		:	E27
Bulb designation		:	T30 (30mm dia.)
Bulb material		:	Hard glass
Bulb finish		:	Frosted (UV-cut coating)
Arc tube material		:	Alumina
Mercury(Hg) content	(mg)	:	5.7
Overall length	(mm)	:	130 max.
Light centre length (Nominal)	(mm)	:	-
Effective arc length (Nominal)	(mm)	:	-



LUMINAIRE DESIGN REQUIREMENTS

Bulb Temp. limit	(°C)	:	430
Base Temp. limit	(°C)	:	230
open / enclosed		:	Open fixture permissible

 **ENERG** Y IJA
IE IA
енергия · ενεργεια

 **IWASAKI** CMT70F/LW925

A⁺⁺
A⁺
A **A**
B
C
D
E

80.3 kWh/1000h