


MR11 with cover glass



PHYSICAL DATA AND CHARACTERISTICS


Type	Ref. ANSI	Volts (V)	Watts (W)	Base	Std. Pkg. Qty.	Axis Cd (cd)	Colour Temp. (K)	Beam Angle (°)	Rated Av. Life (hrs)
JM1161	FTA	12	12	GZ4	50	1500	2800	10	2000
JM1162	—	12	12	GZ4	50	840	2800	20	2000
JM1163	—	12	12	GZ4	50	480	2800	34	2000
JM1261	FTB	12	20	GZ4	50	3750	2950	10	2000
JM1262	FTC	12	20	GZ4	50	1360	2950	20	2000
JM1263	FTD	12	20	GZ4	50	900	2950	34	2000
JM1361	FTE	12	35	GZ4	50	4200	3050	10	3000
JM1362	FTF	12	35	GZ4	50	2350	3050	20	3000
JM1363	FTH	12	35	GZ4	50	1300	3050	34	3000

MR11 low voltage halogen lamp with cover glass.

FEATURES

- Precise optical design.
- Long lasting dichroic coating.
- Reliable long life.
- Suitable for retail stores, lounges, offices, landscape lighting, display cases, homes.

MR11 without cover glass



PHYSICAL DATA AND CHARACTERISTICS

Type	Ref. ANSI	Volts (V)	Watts (W)	Base	Std. Pkg. Qty.	Axis Cd (cd)	Colour Temp. (K)	Beam Angle (°)	Rated Av. Life (hrs)
JM1111	FTA	12	12	GZ4	50	1500	2900	8	2000
JM1112	—	12	12	GZ4	50	500	2900	19	2000
JM1113	—	12	12	GZ4	50	350	2900	25	2000
JM1211	FTB	12	20	GZ4	50	4200	2950	8	2000
JM1212	FTC	12	20	GZ4	50	1450	2950	19	2000
JM1213	FTD	12	20	GZ4	50	700	2950	28	2000
JM1311	FTE	12	35	GZ4	50	6000	3050	10	3000
JM1312	FTF	12	35	GZ4	50	2500	3050	20	3000
JM1313	FTH	12	35	GZ4	50	1350	3050	29	3000

* DC bayonet base is also available.

MR11 low voltage halogen lamp without cover glass.

FEATURES

- Precise optical design.
- Long lasting dichroic coating.
- Reliable long life.
- Suitable for retail stores, lounges, offices, landscape lighting, display cases, homes.